

Jan 2000

| MODEL | PRODUCT DESCRIPTION & FEATURES |
|--|---|
| <p>1233S Offset Pivot Set (Handed) Interior Doors Width to 4'0" (1220)mm Height to 8'0" (2440)mm Weight to 250lbs (113)kg</p> | <ul style="list-style-type: none"> • Bottom pivot mounts directly to floor • Available for fire door assemblies up to three hours (Prefix with "F") • Intermediate pivot required for fire application • Investment cast stainless steel, bearings top and bottom pivot • Available in standard architectural finishes • Extended spindles in 1/2"(12.7)mm increments up to 2"(50.8)mm • Intermediate pivot 1251 suggested see page D-6 |

| MODEL | PRODUCT DESCRIPTION & FEATURES |
|--|---|
| <p>1237S Offset Pivot Set (Handed) Exterior doors Width to 3'6" (1067)mm Height to 7'0" (2134)mm Interior doors Width to 4'0" (1220)mm Height to 8'6" (2590)mm Weight to 600lbs (272kg)</p> | <ul style="list-style-type: none"> • Bottom pivot mounts directly to floor • Available for fire door assemblies up to three hours (Prefix with "F") • Intermediate pivot 1257 required for fire application • Investment cast stainless steel • Available in standard architectural finishes • Extended spindles in 1/2"(12.7)mm increments up to 2"(50.8)mm • Intermediate pivot 1257 suggested see page D-6 |