



**AS895 Angle stop**

- Surface applied stop for single doors
- Large rubber bumper to ensure quiet operation
- Units packed with wood and machine screws to meet most field conditions

**Material substrate**

- Made from 1/8" brass

**Dimensions**

- 1-1/2" wide x 1" angle x 2-1/2" long

**Available accessory items**

- Security pin screws

**Finishes**

| BHMA | Description       | Substrate | Finish |
|------|-------------------|-----------|--------|
| 605  | Bright brass      | Brass     | US3    |
| 606  | Satin brass       | Brass     | US4    |
| 612  | Satin bronze      | Brass     | US10   |
| 613  | Oil rubbed bronze | Brass     | US10B  |
| 625  | Bright chrome     | Brass     | US26   |
| 626  | Satin chrome      | Brass     | US26D  |



**AS18 Angle stop**

- Surface applied stop for single and double doors
- Includes SR64 door silencers to ensure quiet operation
- SR64 silencers are replaceable
- Units packed with wood and machine screws to meet most field conditions

**Material substrate**

- Made from 3/16" brass

**Dimensions**

- 1-1/2" wide x 3/4" angle x 3-1/2" long

**Available accessory items**

- Security pin screws

**Finishes**

| BHMA | Description       | Substrate | Finish |
|------|-------------------|-----------|--------|
| 605  | Bright brass      | Brass     | US3    |
| 606  | Satin brass       | Brass     | US4    |
| 612  | Satin bronze      | Brass     | US10   |
| 613  | Oil rubbed bronze | Brass     | US10B  |
| 625  | Bright chrome     | Brass     | US26   |
| 626  | Satin chrome      | Brass     | US26D  |