

Model 27 3/4" Offset

Application

- Single Acting, Handed
- Exterior or Interior Doors
- Weight to 450 lbs.*
- Door Width up to 4'0" (1219mm)



ANSI/C06041/C06051

* Door size & weight guidelines are determined using the appropriate number of intermediate pivots

Product Description & Features

- Built-in positive dead stop prevents door from swinging beyond the desired opening degree (*specify 85°, 90°, 95°, 105°*)
- Separate and independent valves for closing speed, latch speed and backcheck
- Available non-hold open (N) or selective hold open (S) at same degree as dead stop
- Delayed action option-prefix "DA" (*Non-hold open closers only*)
- Models available to meet ICC/ANSI 117.1 low opening force requirements, prefix "PH". (*For 8-1/2 lbs. of opening force prefix PH and suffix 8-1/2 lbs.*)
- Cold weather fluid available – specify "CWF" (*not available for closers with "DA"*)
- Sealed closer option – specify "SC"
- Available with floor plate or threshold installation (*floor plate shown*)
- Available 1-1/2" offset, for doors with cladding or frames with applied molding, maximum door weight 250 lbs.
- Cicolac, rustproof cement case
- Vertical door adjustment
- Standard top pivot: #180 included
- Intermediate pivot(s) required: M19 (*order separately*), see page 17
- Doors up to 90" (2286mm) in height should use one intermediate pivot. Each additional 30" (762mm) warrants another intermediate pivot
- For fire rated openings (*up to 3 hour assemblies*) prefix "F". This package will be supplied with a steel top pivot (F180) and a non-hold open closer. Intermediate pivot required: FM19 (*order separately*), see page 17
- Fire rated closers cannot have PH option
- For 20-minute labeled doors suffix "-20" to the part number
- Furnished with wood and machine screws
- Extended spindles available in 1/2" increments up to 2" longer than standard

Technical Information

Frame stop required

