

Model 5020

Application

- Double Acting Non-Handed
- Interior Doors
- Weight to 250 lbs.
- Door Sizes up to 4'0" x 8'0" (1219x2438mm)



ANSI/CO6011

Product Description & Features

- Centering arm with adjustment screws in faces of door (*critical for double acting doors*)
- Interchangeable spindle adapters
- Separate and independent valves for closing speed, latch speed and backcheck
- Available non-hold open (N) or automatic hold open (A) specify 90°, 105°
- Delayed action option – prefix "DA" (*non-hold open only*). Closers will not have backcheck
- Auxiliary stop required
- Order spring sizes 3 through 5:

Model	Door Width
5023	36"(914mm)
5024	42"(1067mm)
5025	48"(1219mm)
- Models available to meet ICC/ANSI A117.1 low opening force requirements. Prefix "PH"

Model	Door Width
PH5022	42" (1067mm)
PH5023	48" (1219mm)
- Available with floor plate or threshold installation (*floor plate shown*)
- Cicolac, rustproof cement case
- Arm reinforcement bracket for wood doors – prefix "W"
- Standard top pivot #340 included
- Not allowed for fire rated doors
- Furnished with wood and machine screws
- Extended spindles available in 1/2" increments up to 2" longer than standard

Technical Information

